

HYDRAULIC PUMPS LARIUS SERIES HYDRA INOX

HYDRA 2:1 STAINLESS STEEL REF. 98255

Technical details:

Ratio: 2:1

Motor diameter: 85 mm

Piston stroke: 120 mm

Flow rate: 530 cc/cycle (32 L/min)

Number of max cycles: 60 cycles/min

(hydraulic control with flow rate of 90 l/min requested)

Max supply pressure: 70 bar

Max product pressure: 140 bar

PUMP WITHOUT LINE FILTER

HYDRA 5:1 STAINLESS STEEL REF. 98256

Technical details:

Ratio: 5:1

Motor diameter: 85 mm

Piston stroke: 120 mm

Flow rate: 230 cc/cycle (14 L/min)

Number of max cycles: 60 cycles/min

(hydraulic control with flow rate of 90 l/min requested)

Max supply pressure: 70 bar

Max product pressure: 350 bar

PUMP WITHOUT LINE FILTER

HYDRA 7:1 STAINLESS STEEL REF. 98257

Technical details:

Ratio: 7:1

Motor diameter: 85 mm

Piston stroke: 120 mm

Flow rate: 180 cc/cycle (11 L/min)

Number of max cycles: 60 cycles/min

(hydraulic control with flow rate of 90 l/min requested)

Max supply pressure: 60 bar

Max product pressure: 420 bar

PUMP WITHOUT LINE FILTER

